

SAFETY DATA SHEET

1. Identification

Product identifier	ERTECH™ 2010				
Other means of identification	None.				
Recommended use	Coatings				
Recommended restrictions	None known.				
Manufacturer/Importer/Suppl	ier/Distributor information				
Company Name	ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.				
Address	2829 Lakeland Drive				
	Jackson, MS 39232				
	USA				
After hours telephone number	1-800-222-7122				
Normal work hours telephone number	1-877-982-7667				
Website	www.ergonarmor.com				
E-mail	sds@ergon.com				
Emergency 24-hour telephone number	CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887				
Information on operation hours	8:00 a.m. to 5:00 p.m.				

2. Hazard(s) identification

Physical hazards	Not classified.
Health hazards	Not classified.
Environmental hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	Not available.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	Not applicable.

3. Composition/information on ingredients

м	ixtures
1.1	IALUI C3

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	25 - < 35
QUARTZ		14808-60-7	1 - 5
Other components below re	eportable levels		40 - 100

Other components below reportable level

4. First-aid measures

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

Skin contact	If clothing sticks to the skin, do not remove. Lotion or hand cream may aid in the removal of asphalt. Wash contact areas with soap and water. If needed, seek medical attention.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry chemical powder. Carbon dioxide (CO2).		
Unsuitable extinguishing media	Water. Do not use water jet as an extinguisher, as this will spread the fire.		
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.		
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.		
Fire fighting equipment/instructions	ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.		
Specific methods	In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.		
General fire hazards	No unusual fire or explosion hazards noted.		

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS.			
Methods and materials for containment and cleaning up	This product is miscible in water.			
containing up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas.			
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.			
	Never return spills to original containers for re-use. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.			
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.			
7. Handling and storage				
Precautions for safe handling	Avoid prolonged exposure. Use only in well-ventilated areas. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.			
Conditions for safe storage, including any incompatibilities	Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Do not allow material to freeze.			

8. Exposure controls/personal protection

US. OSHA Table Z-1 Perm Components		Туре			Value	Form
QUARTZ (CAS 14808-60-7)		PEL			0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 Perm	issible Exposu	ire Limi	ts (PEL) for Mine	eral Dusts (
Components		Туре			Value	Form
QUARTZ (CAS 14808-60-7)		TWA			0.1 mg/m3	Respirable.
					2.4 mppcf	Respirable.
US. ACGIH Threshold Lim	it Values (TLV)				
Components		, Туре			Value	Form
ASPHALT (CAS 8052-42-4)		TWA			0.5 mg/m3	Inhalable fume.
QUARTZ (CAS 14808-60-7)		TWA			0.025 mg/m3	Respirable fraction.
NIOSH. Immediately Dan Components	gerous to Life	or Hea Type	lth (IDLH) Value	s, as amen	ded Value	
		IDLH				
QUARTZ (CAS 14808-60-7)			Decemberded		50 mg/m3	
US. NIOSH: Pocket Guide Components		Type	Recommended	Exposure L	Value	Form
ASPHALT (CAS 8052-42-4)		Ceiling	J		5 mg/m3	Fume.
QUARTZ (CAS 14808-60-7)		TWA			0.05 mg/m3	Respirable dust.
ASPHALT (CAS 8052-42-4)	2.5 µg/l		1-Hydroxypyren	Urine	*	
			e, with hydrolysis (1-HP)			
* - For sampling details, plea	ase see the sour	ce docu	()			
propriate engineering ntrols			ntilation, including re limit is not exce		local extraction,	to ensure that the defined
dividual protection measur	es, such as pe	rsonal j	protective equip	ment		
Eye/face protection	Chemical gog goggles).	Chemical goggles and face shield are recommended. Wear safety glasses with side shields (or				
Skin protection						
Hand protection	Chemical resi gloves.	istant gl	oves are recomme	nded. If con	tact with forearm	is likely wear gauntlet sty
Other			thing to prevent a c or rubber gloves,			t and repeated or prolonge
Respiratory protection		When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.				
Thermal hazards	Wear approp	riate the	ermal protective cl	othing, when	n necessary.	
neral hygiene nsiderations	before eating	Always observe good personal hygiene measures, such as washing after handling the material ar before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.				
Physical and chemica	al properties	5				
pearance	Heavy-consis		mulsion.			
Physical state	Liquid.					
Form	Liquid. Visco	us.				

Brown

> 5 - < 7

n/a

Mild Petroleum Odor

Color

Odor threshold

Odor

pН

Melting point/freezing point	n/a	
Initial boiling point and boiling range	212 °F (100 °C)	
Flash point	>212.0 °F (>100.0 °C)	
Evaporation rate	n/a	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or e	xplosive limits	
Explosive limit - lower (%)	n/a	
Explosive limit - upper (%)	n/a	
Vapor pressure	60 mm Hg at 100°F	
Vapor density	n/a	
Relative density	n/a	
Solubility(ies)		
Solubility (water)	Slightly	
Partition coefficient (n-octanol/water)	n/a	
Auto-ignition temperature	>450 °F (>232.22 °C)	
Decomposition temperature	Not available.	
Viscosity	50000 cP at 77°F	
Viscosity temperature	77 °F (25 °C)	
Other information		
Specific gravity	> 1 - < 1.2	
VOC	0.2 lb/gal maximum	

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.		
Chemical stability	Stable under normal temperature conditions.		
Possibility of hazardous reactions	Hazardous polymerization does not occur.		
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not overheat product.		
Incompatible materials	Strong oxidizing agents.		
Hazardous decomposition products	Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen sulfide.		

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.				
Skin contact	No adverse effects due to skin contact are expected.				
Eye contact	May be irritating to eyes.				
Ingestion	Expected to be a low ingestion hazard.				
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.				
Information on toxicological ef	fects				
Acute toxicity					
Product	Species	Test Results			
ERTECH™ 2010					
Acute					
Dermal					

LD50

27109 mg/kg

Rat

Product	Species		Test Results		
Inhalation					
LC50	Rat		16667 mg/l, 6 Hours		
Oral					
LD50	Rat		27202 mg/kg		
Components	Species		Test Results		
ASPHALT (CAS 8052-42-4) Acute					
Dermal					
LD50	Rabbit		> 2000 mg/kg		
Oral					
LD50	Rat		> 5000 mg/kg		
* Estimates for product may t	be based on ad	ditional component data not shown.			
Skin corrosion/irritation	Prolonged ski	in contact may cause temporary irritatio	n.		
Serious eye damage/eye irritation	May be irritat	ing to eyes.			
Respiratory or skin sensitization	on				
Respiratory sensitization	Not available	-			
Skin sensitization	,	in disorders if contact is repeated or pro	5		
Germ cell mutagenicity		No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
Carcinogenicity	This product contains crystalline silica. Silica is a known carcinogen; however in this encapsulated form the normal routes of exposure are unavailable.				
IARC Monographs. Overall	Evaluation o	f Carcinogenicity			
QUARTZ (CAS 14808-60-	ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans. QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)				
QUARTZ (CAS 14808-60-	,	Cancer			
	US. National Toxicology Program (NTP) Report on Carcinogens				
ASPHALT (CAS 8052-42-4 QUARTZ (CAS 14808-60-	7)	Known To Be Human Known To Be Human	-		
•	Not classified				
Specific target organ toxicity - single exposure	Not classified	l.			
Specific target organ toxicity - repeated exposure	Not classified	l.			
Aspiration hazard	Not available				
Chronic effects	Not expected	to be hazardous by OSHA criteria.			
Further information	This product	has no known adverse effect on human	health.		
12. Ecological information	on				
Ecotoxicity	Not expected	to be harmful to aquatic organisms.			
Product		Species	Test Results		
ERTECH™ 2010					
Aquatic					
	EC50	Daphnia	45045.0469 mg/l, 48 hours		
Acute		Dankais			
	EC50	Daphnia	45045.0469 mg/l, 48 hours estimated		
Fish	LC50	Fish	185185.1875 mg/l, 96 hours estimated		
		ditional component data not shown. ailable on the degradability of this prod	uct		

Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

-		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations. No components are identified as hazardous wastes. Disposal recommendations are based on uncontaminated material.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company. Not applicable.	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Avoid discharge into water courses or onto the ground.	
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.	

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7)

Cancer lung effects immune system effects kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No chemical

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ASPHALT (CAS 8052-42-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water ActNot regulated.(SDWA)

California Proposition 65

WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer.



California Proposition 65 - CRT: Listed date/Carcinogenic substance

QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	12-07-2021
Revision date	09-06-2024
Version #	03
Further information	HMIS® is a registered trade and service mark of the NPCA.
NFPA ratings	Health: 1 Flammability: 1 Instability: 0
References	ACGIH EPA: AQUIRE database NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	Physical & Chemical Properties: Multiple Properties