

## SELECTION & SPECIFICATION DATA

<b>Type</b>	Polymer Modified Asphalt
<b>Description</b>	Blackhawk 5800 VersaTak is a preformed compound extruded into rolled strips, and is ideal for sealing cracks and joints in asphalt and concrete pavement. It is also offered in circular pads as a pressure sensitive adhesive to asphalt and concrete pavements for road delineators, rumble strips, parking bumpers and temporary signs.
<b>Uses</b>	<ul style="list-style-type: none"> <li>• Asphalt pavement crack and joint sealer</li> <li>• Concrete pavement crack and joint sealer</li> <li>• Pavement crack and joint bridging compound</li> </ul>
<b>Color</b>	Black
<b>Limitations</b>	VersaTak should not be used on pavement areas that are frequently exposed to solvents and corrosive liquids.

## SUBSTRATES & SURFACE PREPARATION

<b>Pavement</b>	Use a wire brush or similar tool to uproot embedded and loose debris from cracks and seams. Use an air blower or power washer to clear dirt, dust and debris from the crack or seam to ensure a clean, dry surface for proper adhesion. Allow enough time for the pavement to completely dry before applying VersaTak.
-----------------	--

## APPLICATION EQUIPMENT GUIDELINES

Blackhawk 5800 VersaTak can be applied to the paving surface by hand. Where cracks are less than 1/4 in wide, VersaTak can be laid flat over the crack for proper coverage.

Where cracks are 1/4 in or wider, VersaTak can be rolled into ropes and placed in the crack and heated. An additional application of VersaTak can then be laid flat over the crack and heated for added coverage.

## CLEANUP & SAFETY

<b>Cleanup</b>	Allow molten product to cool before cleaning. Mineral spirits or similar solvent may be used for any additional residue.
<b>Safety</b>	Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.
<b>Ventilation</b>	Use in well ventilated areas.

## PACKAGING, HANDLING & STORAGE

<b>Shelf Life</b>	36 months when kept at recommended storage conditions at 75°F (24°C) and in original unopened containers.
<b>Storage Temperature &amp; Humidity</b>	40°F – 90°F (4°C – 32°C) Store at or near 50% relative humidity
<b>Storage</b>	Store indoors. Keep from getting wet. Keep lids on until time of use. Always inspect the product prior to use.
<b>Sizes &amp; Specifications</b>	<p>2.5 in x 50 ft rolls (6 rolls per box, 24 lbs per box, 50 boxes per pallet)</p> <p>4 in x 50 ft rolls (3 rolls per box, 20 lbs per box, 60 boxes per pallet)</p> <p>6 in diameter dots (60 dots per box, 12 lbs per box, 30 boxes per pallet)</p> <p>8 in diameter dots (40 dots per box, 14 lbs per box, 30 boxes per pallet)</p>

Rev 09/19

### TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see [ergonarmor.com](http://ergonarmor.com).