

SELECTION & SPECIFICATION DATA

| | |
|-----------------------|--|
| Type | Tacky Acrylic Emulsion |
| Description | Blackhawk Hawk-Tack is a high tack acrylic emulsion primer. It can be applied to masonry, gypsum board, concrete, wood, and a variety of other surfaces. It is the product of choice when it is necessary to achieve fast drying, solvent free, tacky surfaces. |
| Features | <ul style="list-style-type: none"> • Quick drying • Tacky film provides positive adhesion of membranes • Easily applied by brush, spray or roller • Environmentally friendly low VOC • Non-flammable during application • Water-based, no solvent odor |
| Uses | Blackhawk Hawk-Tack is designed to be used as a surface adhesion promoter with modified bitumen self-adhering membranes, or where a tacky surface is required. |
| Color | White. Custom colors available. |
| Finish | Blackhawk Hawk-Tack has a tacky/gloss finish. Color tinted material helps to indicate application area. |
| Solids Content | 60 ± 2% by weight |
| VOC Value(s) | <25 grams per liter (0.2 lbs per gallon) |
| Limitations | Keep from freezing |

SURFACE & PRODUCT PREPARATION

| | |
|------------|--|
| All | All surfaces must be clean and free from debris and loose scale material or anything that may interfere with adhesion or act as a bond breaker with the desired substrate. |
|------------|--|

SAFETY

| | |
|--------------------|--|
| Safety | Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using. |
| Ventilation | Thorough air circulation must be used during and after application until the product is cured. User should test and monitor exposure levels to ensure all personnel are within safe limits. Consult product SDS for further information. |

MIXING & THINNING

| | |
|-----------------|---|
| Mixing | Mix material before use to ensure uniformity. |
| Thinning | Use as supplied. Water reducible if situations dictate. |
| Cleanup | Mineral spirits |

APPLICATION GUIDANCE

| | |
|--------------------------------|---|
| Brush | Apply with a wide fiber brush in order to create a smooth uniform film. |
| Roller | Use a low nap phenolic core roller. |
| Drying Time | Initial set: 30 minutes at 68°F (20°C) Full set: 2 hours 68°F (20°C) |
| Application Temperature | 45°F – 110°F (7.2°C – 43.3°C) |

PACKAGING, HANDLING & STORAGE

| | |
|----------------------------------|--|
| ITEM # | PACKAGING |
| K-7000-275-001 | Tote - 270 gallons |
| Theoretical Coverage Rate | 300 - 400 square feet at 4 to 5 wet mils |
| Storage & Shelf Life | Estimated shelf life is 6 months when stored in a dry area at 75°F (24°C). Actual shelf life may vary with storage conditions. Do not store below 50°F (10°C) or above 110°F (43°C). Store Indoors. Protect from freezing. |

TYPICAL PHYSICAL PROPERTIES

| | |
|--------------------------|-----------------------------|
| Flammability | Wet nonflammable, dry burns |
| Flash Point | >212°F (100°C) |
| Viscosity | 2,000 – 4,000 cps |
| Weight Per Gallon | 8.0 – 9.2 lbs |

Rev 12/21

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see ergonarmor.com.