SAFETY DATA SHEET



1. Identification

Product identifier PENNTROWEL™ WATER CLEANABLE EPOXY GROUT RESIN

Other means of identification None.

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

Normal work hours

telephone number

1-877-982-7667

1-800-222-7122

Website www.ergonarmor.com
E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Sensitization, skin Category 1

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment, Category 2

long-term hazard

OSHA defined hazards Not classified.

Label elements





Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting

effects.

Precautionary statement

Prevention Avoid breathing dust/fume/qas/mist/vapors/spray. Wear protective gloves/protective clothing.

Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of

the workplace.

Response Wash hands after handling. Collect spillage. IF ON SKIN: Wash with plenty of soap and water. If

skin irritation or rash occurs: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed.

Disposal Dispose of contents/container to an appropriate treatment and disposal facility in accordance with

applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
BISPHENOL A-(EPICHLOROHYDRIN) EPOXY RESIN		25068-38-6	70 - < 80
[(TOLYLOXY)METHYL]OXIRANE		26447-14-3	0 - 40
1-METHOXYPROPAN-2-OL		107-98-2	5 - < 10

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for

breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a

one-way valve or other proper respiratory medical device. Call a POISON CENTER or

doctor/physician if you feel unwell.

Skin contact Remove and isolate contaminated clothing and shoes. Wash off with soap and plenty of water. For

minor skin contact, avoid spreading material on unaffected skin. Get medical attention if irritation

develops and persists. Wash clothing separately before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Do not induce vomiting. Do not use mouth-to-mouth method if victim ingested the substance. IF

SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Upper respiratory tract irritation. Irritation of nose and throat. Irritation of eyes and mucous membranes. Prolonged exposure may cause chronic effects. May cause allergic skin reaction.

Irritant effects.

Not available.

Indication of immediate medical attention and special treatment needed

In case of shortness of breath, give oxygen. Symptoms may be delayed.

General information If you feel unwell, seek medical advice (show the label where possible). Wash contaminated

clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water spray. Water fog. Foam. Carbon dioxide (CO2). Powder.

Unsuitable extinguishing media

Specific hazards arising from the chemical

No unusual fire or explosion hazards noted.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk. Water runoff can cause environmental damage.

Specific methods In the event of fire, cool tanks with water spray. Move container from fire area if it can be done without risk.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Avoid inhalation of vapors or mists. Avoid skin contact and inhalation of vapors during disposal of spills.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth or absorbent material then place into containers. Prevent product from entering drains.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Do

not get this material in contact with skin. Do not get this material on clothing. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Avoid prolonged

exposure. Wash hands thoroughly after handling. Avoid release to the environment.

Conditions for safe storage,

including any incompatibilities

Store in a well-ventilated place. Store in original tightly closed container. Store in a closed

container away from incompatible materials. Store in accordance with

local/regional/national/international regulation.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values (TLV)

Components	Туре	Value	
1-METHOXYPROPAN-2-OL (CAS 107-98-2)	STEL	100 ppm	
	TWA	50 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value 1-METHOXYPROPAN-2-OL (CAS 107-98-2) STEL 540 mg/m3 150 ppm TWA 360 mg/m3

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

1-METHOXYPROPAN-2-OL (CAS 107-98-2) Can be absorbed through the skin.

Appropriate engineering

controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

100 ppm

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Do not get in eyes. Chemical goggles are recommended.

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear quantilet style

gloves.

Other Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Not available.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes. Avoid contact with eyes. Avoid contact with skin. Avoid contact with clothing. Wash hands after handling. Wash hands before breaks and immediately after handling the product. Wash hands after handling and before eating. Keep away from food and drink. Contaminated work clothing should not be allowed out of the

workplace. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance Liquid.

Physical state Liquid.

Form Liquid.

Color Colourless to light yellow.

Odor Mild.

Odor threshold

pH

Not available.

Melting point/freezing point

Initial boiling point and
boiling range

Not available.

Not available.

Material name: PENNTROWEL™ WATER CLEANABLE EPOXY GROUT RESIN
5279 Version #: 02 Revision date: 07-22-2024 Issue date: 05-23-2023

Flash point >100.0 °F (>37.8 °C)

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure Not available. Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

518 °F (270 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. Not available. Viscosity

Other information

Specific gravity 1.17

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

This product will autopolymerize at very high temperatures. (>200 deg C)

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point.

Strong acids, alkalis and oxidizing agents. Amines. Incompatible materials

Hazardous decomposition

products

Toxic gas. Irritants.

11. Toxicological information

Information on likely routes of exposure

Inhalation Inhalation of vapors/fumes generated by heating this product may cause respiratory irritation with

throat discomfort, coughing or difficulty breathing.

Skin contact May cause sensitization by skin contact. Causes skin irritation.

Eye contact Causes eye irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Upper respiratory tract irritation. Irritation of nose and throat. Irritant effects.

Information on toxicological effects

Acute toxicity Not applicable.

Components **Species Test Results**

[(TOLYLOXY)METHYL]OXIRANE (CAS 26447-14-3)

Acute

Dermal

LD50 Rat > 2000 mg/kg

Inhalation

LC50 Rat > 6.1 mg/l, 4 Hours

Oral

> 5000 mg/kg LD50 Rat

Material name: PENNTROWEL™ WATER CLEANABLE EPOXY GROUT RESIN 5279 Version #: 02 Revision date: 07-22-2024 Issue date: 05-23-2023 Components **Species Test Results**

1-METHOXYPROPAN-2-OL (CAS 107-98-2)

Acute

Dermal

LD50 Rabbit 13 - 14 g/kg

Inhalation

LC50 Rat 54.6 mg/l, 4 Hours

Oral

LD50 Rat 5.71 g/kg

Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye

May be irritating to eyes.

irritation

Respiratory or skin sensitization

Not available. **Respiratory sensitization**

Skin sensitization May cause sensitization by skin contact. May cause an allergic skin reaction.

Germ cell mutagenicity Not classified. Carcinogenicity Not assigned.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Not available. Not classified. Reproductive toxicity

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not applicable.

Aspiration hazard Not classified.

Chronic effects Hazardous by OSHA criteria. Prolonged exposure may cause chronic effects.

Further information Symptoms may be delayed.

12. Ecological information

Ecotoxicity Accumulation in aquatic organisms is expected. Contains a substance which causes risk of

hazardous effects to the environment. Harmful to aquatic life with long lasting effects. The product

contains a substance which is harmful to aquatic organisms.

Product Species **Test Results**

PENNTROWEL™ WATER CLEANABLE EPOXY GROUT RESIN

Aquatic

Crustacea EC50 Daphnia 3.6178 mg/l, 48 hours Fish 2.0099 mg/l, 96 hours LC50 Fish

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

1-METHOXYPROPAN-2-OL -0.49

Mobility in soil Not available. Other adverse effects Not available.

^{*} Estimates for product may be based on additional component data not shown.

^{*} Estimates for product may be based on additional component data not shown.

13. Disposal considerations

Disposal instructions Do not discharge into drains, water courses or onto the ground. This product, in its present state,

> when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the

time of disposal, whether the product meets RCRA criteria for hazardous waste.

Hazardous waste code Not applicable.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions). Avoid discharge into water courses or onto the ground.

FLAMMABLE LIQUID, N.O.S. (1-METHOXYPROPAN-2-OL), MARINE POLLUTANT

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

UN number

UN proper shipping name

Flammable liquid, n.o.s. (1-METHOXYPROPAN-2-OL)

Transport hazard class(es) Class

Subsidiary hazard Packing group III **Environmental hazards** YES 3L

ERG Code

Special precautions for

user Other information Not assigned.

3

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN1993

UN proper shipping name Transport hazard class(es)

Class 3

Subsidiary hazard Packing group III

Environmental hazards

Marine pollutant Yes

F-E, S-E **EmS** Special precautions for Not assigned.

user

Transport in bulk according to Annex II of MARPOL 73/78

and the IBC Code

Not available.

IATA; IMDG



Marine pollutant



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

1-METHOXYPROPAN-2-OL (CAS 107-98-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Skin corrosion or irritation Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer and

birth defects or other reproductive harm.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1-METHOXYPROPAN-2-OL (CAS 107-98-2)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes

Country(s) or region On inventory (yes/no)* **Inventory name**

New Zealand New Zealand Inventory Yes **Philippines** Yes

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Chemical Substance Inventory (TCSI) Taiwan Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 05-23-2023 Revision date 07-22-2024

Version # 02

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 2

Flammability: 1 Instability: 0

References **ACGIH**

EPA: AQUIRE database

NLM: Hazardous Substances Data Base HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

US. IARC Monographs on Occupational Exposures to Chemical Agents

The information provided in this Safety Data Sheet is correct to the best of our knowledge, Disclaimer

> information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any

other materials or in any process, unless specified in the text.

Revision information Hazard(s) identification: Supplemental information

> Physical & Chemical Properties: Multiple Properties Stability and reactivity: Incompatible materials

Stability and reactivity: Reactivity

GHS: Classification

Material name: PENNTROWEL™ WATER CLEANABLE EPOXY GROUT RESIN 5279 Version #: 02 Revision date: 07-22-2024 Issue date: 05-23-2023